

# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY

**SUBSTANCE NAME:** Paint Stripper  
**PARTS NO:** 3051053  
**COMPANY IDENTIFICATION:** CLARKE INTERNATIONAL,  
HEMNALL STREET, EPPING, ESSEX. CM16 4LG  
**BUSINESS TELEPHONE:** 01992 565300  
**BUSINESS FAX:** 01992 561562  
**EMERGENCY TELEPHONE:** 020 89887400

## 2. COMPOSITION/INFORMATION ON INGREDIENTS:

### Hazardous Ingredients

	Conc.	CAS	EINECS	Risks
Methanol	1-10%	67-56-1	200-659-6	F; R11 T; R23/24/25-39/23/24/25
Methylene chloride (Dicloromethane)	70-80%	75-09-2	200-838-9	Carc Cat 3; R40
METHOCYL	1-10%			
Xylene (Xylene, o-,m-,p-or mixed isomers)	1-10%	1330-20-7	215-535-7	R10 Xn; R20/21 Xi; R38
PARAFFIN WAX (Paraffin wax, fume)	1-10%	8002-74-2		

## 3. HAZARDS IDENTIFICATION:

**Main hazards** Harmful by inhalation, in contact with skin and if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect.

## 4. FIRST AID MEASURES:

**Skin contact** Causes burns. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

**Eye contact** Causes burns. Causes severe inflammation and may damage the cornea. Seek medical attention.

**Inhalation** Inhalation of vapour may cause shortness of breath. Move the exposed person to fresh air. Seek medical attention.

**Ingestion** Ingestion causes burns to the respiratory tract. DO NOT INDUCE VOMITING. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. If swallowed, seek medical advice immediately and show this container or label.

## 5. FIRE FIGHTING MEASURES:

**Extinguishing media** Alcohol resistant foam. Carbon dioxide (CO2).

**Fire hazards** Corrosive. Burning produces irritating, toxic and obnoxious fumes.

**Protective equipment** Self-contained breathing apparatus. Wear protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES:

**Personal precautions** Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment.

**Environmental precautions** Do not allow product to enter drains. Prevent further spillage if safe.

**Clean up methods** Absorb with inert, absorbent material. Transfer to suitable labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## 7. HANDLING & STORAGE:

**Handling** Avoid contact with eyes and skin. Ensure adequate ventilation of the working area.

# SAFETY DATA SHEET

## Storage

Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

### Exposure limits

Methanol	WEL 8-hr limit ppm: 200 WEL 15 min limit ppm: 250	WEL 8-hr limit mg/m3: 266 WEL15 min limit mg/m3: 333
Methylene chloride (Dichloromethane)	WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 300	WEL 8-hr limit mg/m3: 350 WEL 15 min limit mg/m3: 1060
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 220 WEL 15 min limit mg/m3: 441
PARAFFIN WAX (Paraffin wax, fume)	WEL 8-hr limit ppm:- WEL 15 min limit ppm:-	WEL 8-hr limit mg/m3: 2 WEL 15 min limit mg/m3: 6

<b>Engineering measures</b>	Ensure adequate ventilation of the working area.
<b>Respiratory protection</b>	Self-contained breathing apparatus must be used in handling.
<b>Hand protection</b>	Chemical resistant gloves (PVC).
<b>Eye protection</b>	Approved safety goggles.
<b>Protective equipment</b>	Wear chemical protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES:

<b>Description</b>	Liquid
<b>Colour</b>	Brown
<b>Odour</b>	Phenolic

## 10. STABILITY AND REACTIVITY:

<b>Stability</b>	Stable under normal conditions.
------------------	---------------------------------

## 11. TOXICOLOGICAL INFORMATION:

<b>Acute toxicity</b>	Harmful by inhalation, in contact with skin and if swallowed. May cause dizziness and headache. Toxic by inhalation. Toxic if swallowed.
<b>Corrosivity</b>	Causes burns. May cause degreasing of the skin. May cause severe irritation to skin, eyes and mucous membranes. Risk of serious damage to eyes.

## 12. ECOLOGICAL INFORMATION:

<b>Ecotoxicity</b>	May cause long-term adverse effects in the aquatic environment.
--------------------	---

<b>Degradability</b>	Evaporates readily.
----------------------	---------------------

## 13. DISPOSAL CONSIDERATIONS:

<b>General information</b>	Dispose of in compliance with all local and national regulations.
----------------------------	---

## 14. TRANSPORT INFORMATION:

### ADR/RID

UN 2810	<b>Packing group II</b>
Class 6.1	<b>Hazard ID 60</b>
<b>Proper Shipping:</b> TOXIC LIQUID ORGANIC Name N.O.S	

### IMDG

UN 2810	<b>Packing group II</b>
Class 6.1	<b>Marine pollutant</b>
<b>EmS Code</b> F-A S-A	

### IATA

UN 2810	<b>Packing Group II</b>
Class 6.1	<b>Subsidiary risk –</b>
<b>Packing Instruction 611</b> (Cargo)	<b>Maximum quantity 60 L</b>
<b>Packing Instruction 609</b> (Passenger)	<b>Maximum quantity 5 L</b>

# SAFETY DATA SHEET

## 15. REGULATORY INFORMATION:

**Labelling** The product is classified in accordance with 67/548/EEC.  
**Symbols** T - Toxic



**Risk phrases** R20/21/22 – harmful by inhalation, in contact with skin and if swallowed.  
R39/23/24/25 – Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.  
R40 – Limited evidence of a carcinogenic effect

**Safety phrases** S23 – Do not breathe gas/fumes/vapour/spray  
S27 – Take off immediately all contaminated clothing  
S38 – In case of insufficient ventilation, wear suitable respiratory equipment  
S61 – Avoid release to the environment. Refer to special instructions/safety data sheets.  
S36/37 – Wear suitable protective clothing and gloves.  
S45 – In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

## 16. OTHER INFORMATION

**Text of risk phrases** R10 – Flammable.  
**Section 2** R11 – Highly flammable  
R20/21 – Harmful by inhalation and in contact with skin  
R23/24/25 – Toxic by inhalation, in contact with skin and if swallowed  
R38 – Irritating to skin  
R39/23/24/25 – Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed  
R40 – Limited evidence of a carcinogenic effect

**Further information** The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.