

| Model Identifier(s): BGP1402-03 (Devil 2800) |                    |   |      |   |      |
|--|--------------------|---|------|---|------|
| Item   | Symbol             | Value   | Unit | Item  | Unit |
| Heat Output                                  |                    |   |      | <b>Type of heat input for electric storage space heaters only (select one).</b> |      |
| Nominal heat output                          | P <sub>nom</sub>   | 3.0   | kW   | manual heat charge control, with integrated thermostat                          | no   |
| Minimum heat output (indicative)             | P <sub>min</sub>   | 1.5   | kW   | manual heat charge control, with room and / or outdoor temperature feedback     | no   |
| Maximum Continuous heat output               | P <sub>max,c</sub> | 3   | kW   | electronic heat charge control with room and / or outdoor temperature feedback  | no   |
| <b>Auxiliary electricity consumption</b>     |                    |   |      | fan assisted heat output  |      |
| At nominal heat output                       | e <sub>l,max</sub> | N/A   | kW   | <b>Type of heat output/ room temperature control (select one)</b>               |      |
| At minimum heat output                       | e <sub>l,min</sub> | N/A   | kW   | single stage heat output and no room temperature control                        | no   |
| In standby Mode                              | e <sub>l,SB</sub>  | N/A   | kW   | two or more manual stages, no room temperature control                          | no   |
|  |                    |   |      | with mechanic thermostat room temperature control                               | yes  |
|  |                    |   |      | with electronic room temperature control  | no   |
|  |                    |   |      | with electronic room temperature control plus day timer                         | no   |
|  |                    |   |      | with electronic room temperature control plus week timer                        | no   |
|  |                    |   |      | <b>Other control options (mutiple selections possible)</b>                      |      |
|  |                    |   |      | room temperature control, with presence detection                               | no   |
|  |                    |   |      | room temperature control, with open window detection                            | no   |
|  |                    |   |      | with distant control option   | no   |
|  |                    |   |      | with adaptive start control   | no   |
|  |                    |   |      | with working time limitation  | no   |
|  |                    |   |      | with black bulb sensor  | no   |
| <b>Contact Details</b>                       |                    | Clarke International , 28 Hemnall Street, Epping, CM1 4LG |      |   |      |