

**ERP Technical Information**

**Clarke Model:** COB10C  
**Model Type:** L9601P  
**General Description** 10W COB LED light Carry handle

**Reference to harmonised Standards**

EN 60598-1:2015  
EN 60598 -2-4:1997  
EN 60598-2-5:1998  
EN 62493:2015  
IEC 62778:2014  
EN 55015:2013  
EN 61547:2009  
EN 61000-3-2:2013  
EN 61000-3-3:2013

**Specific Precautions**

Portable LED Floodlight to be used indoors or outdoors.  
To be operated as prescribed by the Clarke Operating Manual

**Measured Technical Parameters**

Operating Voltage (AC / Hz)	230 / 50
Operating Temperatures: (Min / Max °C)	- 20 to 50
LED Wattage Consumption	10
Luminous Flux: (Lm)	800
Efficiency (Lm / W)	80
Energy Efficiency Class:	A+
Weighted Energy Consumption	10kWh/1000h
LED Lifetime:	20000 hrs
Colour Temperature:	6500 K
Stand:	Floor stand and carry handle
IP Rating:	IP65
Insulation Class:	I
Tilt adjustment:	- 90°C to 90°C
Product weight(Kg):	1.1
Type of light:	Flood light
LED Manufacturer:	Epistar LED Chip