

**ERP Technical Information**

**Clarke Model NO:** HLC400/110  
**Model Type:** 0203/110  
**General Description** 400 W (110V) halogen floodlight with handle & grill

**Reference to harmonised Standards**

- EN 60598-1:2015
- EN 60598-2-5:1998
- EN 60598-2-7:1989+A2:1996+A13+1997
- EN 62493:2010
- EN 62321:2009

**Specific Precautions**

For internal or external use. To be operated as prescribed by the Clarke Operating Manual.  
To provide light for use on construction site and similar application  
The distance between the item and the object must be more than 1 m.  
Suitable for domestic or trade use.  
sample have a fixed height at floor level

**Measured Technical Parameters**

Operating Voltage (V/dc) (USB)	110 AC / 60 Hz
Operating Temperatures: (Min / Max °C)	-20 to 50
LED Wattage Consumption	400W
IP rating:	IP54
Luminous Flux: (Lm)	8,545
Efficiency (Lm / W)	21.4
Energy Efficiency Class:	C Class Tube
Stand:	U-type stand, handle connected with the stand
Tilt adjustment:	head rotation -90° C ~ 90 °C
Product weight(Kg):	1.5
Supply cable plug type:	16A-4H/100- 130V 50 ~60 Hz 2P+E and IP44BS EN60309
Bulb lifetime	1000h
Colour Temperature:	2900K
LED Type:	Halogen Tube R7s - J118
Type of light:	Flood light