

ERP Technical Information

Clarke Model: HLC400T
Model Type: 0208A-2
General Description Double 400W (230V)Twin Halogen flood light and grill with Tripod

Reference to harmonised Standards

EN 60598-1:2015
EN 60598-2-5:1998
EN 60598-2-7:1989+A2:1996+A13+1997
EN 62493:2010
EN 62321:2009

Specific Precautions

To provide light for domestic use
To be operated as prescribed by the Clarke Operating Manual.
The distance between the item and the object must be more than 1m
Sample can be used with or without a tripod
Do not use at construction sites
This lamp is sold with 2 bulbs of energy class C.
Temperature resistant label must be attached to warn the user not to touch the hot surface.

Measured Technical Parameters

Operating Voltage (V / Hz)	230 / 50
Operating Temperatures: (Min / Max °C)	-20 to 50
Rated Input Current (A):	3.5
Lifetime(h):	1000
Insulation class:	I,II,III
IP rating:	IP54
Luminous Flux: (Lm)	2x 8545
LED replaceable:	Yes
Efficiency (Lm / W)	21.4
Energy Efficiency Class:	C class tube
Weighted energy Consumption: kWh /1000h	400kWh/1000
Colour Temperature (K):	2x 2900
Stand:	Tripod stand and Handle Fixings
Tilt adjustment (°):	95 vertically & 180 Horizontally
Product weight(Kg):	5.25
On - off Switch Type:	No switch
Supply Cable Plug Type:	A 13 Amp BS1363
Type of light:	Flood Light:
LED Manufacturer:	Cixi Zhongfa Lamps Co Ltd
LED Model:	Halogen Tube - socket size R7s