

**ERP Technical Information**

**Clarke Model NO:** SMD42C  
**Model Type:** L3305S  
**General Description** 42SMD LED Light 21 W, carry Handle, Portable LED floodlight

**Reference to harmonised Standards**

EN 60598-1:2015  
EN 60598-2-4:1997  
EN 605982-5:1998  
EN 62493:2015  
IEC 62778:2014  
EN55015:2013  
EN61547:2009  
EN61000-3-2:2014  
EN61000-3-3:2013

**Specific Precautions**

Portable LED Floodlight to be used indoors or outdoors.  
To be operated as prescribed by the Clarke Operating Manual.

**Measured Technical Parameters**

Operating Voltage (V/Hz)	230 / 50
Operating Temperatures: (Min / Max °C)	-20 to 50
LED Wattage Consumption	21W
Luminous Flux: (Lm)	1650
LED Manufacturer:	Epistar LED chip
LED Replaceable:	No
Efficiency (Lm / W)	79
Energy Efficiency Class:	A+
Insulation class:	II
Stand:	Floor stand and carry handle
Colour temperature (K):	6500
Tilt adjustment:	N/A
Weighted energy Consumption: kWh/1000h	21
Product weight(Kg):	1.2
Life Expectancy (hr):	20000
Supply Cable Plug type:	BS Moulded 3 pin 13A
Type of Light:	Flood light