

ERP Technical Information

Clarke Model: SMD42T/110
Model Type: L3305SJ
General Description 42SMD LED light 21W Tripod, 110V
Portable LED flood light that can be used both indoors and outdoors.

Reference to harmonised Standards

EN 60598-1:2015
EN 60598-2-4:1997
EN 60598-2-5:1998
EN 62493:2015
IEC 62778:2014
EN 55015:2013
EN 61547:2009
EN 61000-3-2:2014
EN 61000-3-3:2013

Specific Precautions

Portable LED flood light to be used indoors or outdoors.
To be operated as prescribed by the Clarke Operating manual.

Measured Technical Parameters

Operating Voltage (V / Hz)	110 / 50
Operating Temperatures: (Min / Max °C)	-20 to 50
Rated Input Power:	21
Lifetime(h):	20000 hrs
Luminous Flux: (Lm)	1650
Efficiency (Lm / W)	80
Energy Efficiency Class:	A+
Colour Temperature (K):	6500
Stand:	Tripod
IP rating:	IP54
Insulation class:	II
Tilt adjustment (°):	-90 to 90
Product weight(Kg):	3.5
On - off Switch Type:	Rocker Switch
Supply Cable Plug Type:	3 pin industrial plug to EN60309 16A
LED Manufacturer:	Epistar LED chip
Type of Light:	Led Floodlight