

Clarke®

air

1/4" MINI AIR FILTER INSTRUCTIONS FOR USE

Model Number MF2

Part No; 5100810

GUARANTEE

This CLARKE product is guaranteed against faulty manufacture for a period of 12 months from the date of purchase. Please keep your receipt as proof of purchase.

This guarantee is invalid if the product is found to have been abused or tampered with in any way, or not used for its intended purpose.

Faulty goods should be returned to their place of purchase, no product can be returned to us without prior permission.

This guarantee does not effect your statutory rights.

This filter unit is built to operate in an environment in which the temperature does not exceed +60°F and the air is not contaminated with solvents to such an extent as to cause irreversible damage to components.

NEVER use solvents to clean the filter unit as this would cause irreversible damage to the polycarbonate bowl. Use dishwashing liquid for cleaning.

Take care when connecting the unions to the unit, do not overtighten. The filter should ideally be connected to a fixed airline or mounted on the outlet of the compressor.

The maximum supply pressure the unit can operate is 145psi (10bar).

An arrow, moulded on the top of the unit, indicates the direction in which the air should flow.

IMPORTANT! You are reminded that the sequence for airline component assembly is: FILTER - LUBRICATOR.

Condensate is collected in the polycarbonate bowl, and will eventually become visible. This will drain automatically when the air pressure is turned off. The external stem of the drain valve is a 4.5mm hose tail, where a hose can be fitted to drain off the water.

There are no user serviceable parts on this unit.

GC1109

Clarke®

air

1/4" MINI AIR FILTER INSTRUCTIONS FOR USE

Model Number MF2

Part No; 5100810

GUARANTEE

This CLARKE product is guaranteed against faulty manufacture for a period of 12 months from the date of purchase. Please keep your receipt as proof of purchase.

This guarantee is invalid if the product is found to have been abused or tampered with in any way, or not used for its intended purpose.

Faulty goods should be returned to their place of purchase, no product can be returned to us without prior permission.

This guarantee does not effect your statutory rights.

This filter unit is built to operate in an environment in which the temperature does not exceed +60°F and the air is not contaminated with solvents to such an extent as to cause irreversible damage to components.

NEVER use solvents to clean the filter unit as this would cause irreversible damage to the polycarbonate bowl. Use dishwashing liquid for cleaning.

Take care when connecting the unions to the unit, do not overtighten. The filter should ideally be connected to a fixed airline or mounted on the outlet of the compressor.

The maximum supply pressure the unit can operate is 145psi (10bar).

An arrow, moulded on the top of the unit, indicates the direction in which the air should flow.

IMPORTANT! You are reminded that the sequence for airline component assembly is: FILTER - LUBRICATOR.

Condensate is collected in the polycarbonate bowl, and will eventually become visible. This will drain automatically while the air supply is turned off. The external stem of the drain valve is a 4.5mm hose tail, where a hose can be fitted to drain off the water.

There are no user serviceable parts on this unit.

GC1109

A SELECTION FROM THE VAST RANGE OF

Clarke®

QUALITY PRODUCTS

AIR COMPRESSORS

From DIY to industrial, Plus air tools, spray guns and accessories.

GENERATORS

Prime duty or emergency standby for business, home and leisure.

POWER WASHERS

Hot and cold, electric and engine driven - we have what you need

WELDERS

Mig, Arc, Tig and Spot. From DIY to auto/industrial.

METALWORKING

Drills, grinders and saws for DIY and professional use.

WOODWORKING

Saws, sanders, lathes, mortisers and dust extraction.

HYDRAULICS

Cranes, body repair kits, transmission jacks for all types of workshop use.

WATER PUMPS

Submersible, electric and engine driven for DIY, agriculture and industry.

POWERTOOLS

Angle grinders, cordless drill sets, saws and sanders..

STARTERS/CHARGERS

All sizes for car and commercial use.



PARTS & SERVICE: 0208 988 7400

E-mail: Parts@clarkeinternational.com or Service@clarkeinternational.com

SALES: UK 01992 565333 or Export 00 44 (0)1992 565335

Clarke INTERNATIONAL Hemnall Street, Epping, Essex CM16 4LG
www.clarkeinternational.com

A SELECTION FROM THE VAST RANGE OF

Clarke®

QUALITY PRODUCTS

AIR COMPRESSORS

From DIY to industrial, Plus air tools, spray guns and accessories.

GENERATORS

Prime duty or emergency standby for business, home and leisure.

POWER WASHERS

Hot and cold, electric and engine driven - we have what you need

WELDERS

Mig, Arc, Tig and Spot. From DIY to auto/industrial.

METALWORKING

Drills, grinders and saws for DIY and professional use.

WOODWORKING

Saws, sanders, lathes, mortisers and dust extraction.

HYDRAULICS

Cranes, body repair kits, transmission jacks for all types of workshop use.

WATER PUMPS

Submersible, electric and engine driven for DIY, agriculture and industry.

POWERTOOLS

Angle grinders, cordless drill sets, saws and sanders..

STARTERS/CHARGERS

All sizes for car and commercial use.



PARTS & SERVICE: 0208 988 7400

E-mail: Parts@clarkeinternational.com or Service@clarkeinternational.com

SALES: UK 01992 565333 or Export 00 44 (0)1992 565335

Clarke INTERNATIONAL Hemnall Street, Epping, Essex CM16 4LG
www.clarkeinternational.com